Georg Koinzer
Conveyor belts for the textile industry

Questionnaire - Spiked Lattice PAT5030

Type of machine		Part-No.	
Manufacturer		Year	

Length of **belt** ☐ mm measured over shafts

Distance from lath center - lath center ☐ mm

Length of **laths** ☐ mm

Web strips between laths for sealing?
☐ yes (standard)
☐ no



Number of **belts** ☐ pieces

Width of belts ☐ mm

Division of belts middle - middle
☐ equal distribution and flush on the outside
☐ according to special design:

Belt 1	Belt 2	Belt 3	Belt 4	Belt 5	Belt 6	Belt 7

Endless connection
☐ endless welded
☐ screwed overlapping connection

Pins	Diameter	Protruding pin length
☐	5,4 x 53 mm	ca. 28,5 mm
☐	5,4 x 63 mm	ca. 38,5 mm
☐	special design on request	

Pin design
☐ standard
☐ stainless steel (upon request)

Pins in gearing with other belts or shafts?
☐ Yes
☐ No

Pin angle (45° Standard) ☐ degrees

Position of the pins
☐ staggered
☐ in rows

Pin pith = distance pin to pin ☐ mm

Distance from end of lath to the first pin

	left mm	right mm	No. of pins
Lath 1			
Lath 2			

Specialities

Inquiry from		Georg Koinzer GmbH & Co. KG
Street		Robert-Bunsen-Straße 15
Zip code/location		36179 Bebra
Contact person		
Phone		Phone +49 6622 - 9284 - 0
Email		Email sales@gkoinzer.de