

# Questionnaire - Spiked lattice PAS3020

Type of machine   
 Manufacturer  Part-No.   
 Year

Inner length of **belt**  mm measured over shafts Distance lath centre  mm Standard  
 - lath centre  mm

Length of **laths**  mm

**Web strips** between laths for sealing? yes (standard)  
 no

Belts Transilon belt  
 Toothed belt  
 Toothed belt with intermediary

Number of **belts**  pieces

Width of belts  mm

Division of belts middle - middle equal distribution and flush on the outside  
 according to special design:



Endless connection endless welded  
 screwed overlapping connection

**Pins**  mm diameter  mm length  
 mm protruding pin length

Pin design standard Pins in gearing with other belts or shafts? Yes  
 stainless steel (on request) No  
 sheradized (=very durable galvanisation)

Pin degree  degree Position of pins staggered  
 degree in rows

Pin pitch = distance pin to pin  mm

	left mm	right mm	number of pins
Lath 1	<input type="text"/>	<input type="text"/>	<input type="text"/>
Lath 2	<input type="text"/>	<input type="text"/>	<input type="text"/>

Specialities

Inquiry from	<input type="text"/>	Georg Koinzer GmbH & Co. KG Robert-Bunsen-Straße 15 36179 Bebra  Phone +49 6622 - 9284 - 0 Email sales@gkoinzer.de
Street	<input type="text"/>	
Zip Code/location	<input type="text"/>	
Contact person	<input type="text"/>	
Phone	<input type="text"/>	
Email	<input type="text"/>	