

# Questionnaire - Spiked Lattice PE-HYG

Type of machine  Part-No.   
 Manufacturer  Year

Inner length of **belt**  mm measured over shafts distance lath centre  mm Standard  
 - lath centre

Length of **laths**  mm

Profile of laths 25 x 12 mm trapeze  
 30 x 20 mm trapeze  
 Special design

**Web strips** between laths for sealing? yes (standard) no Intermediary lath (sealing) Yes (Standard) No

Number of **belts**  pieces Belts transilon belt  
 Width of belts  mm toothed belt  
 toothed belt with intermediary

Division of belts middle - middle equal distribution and flush on the outside  
 according to special design:  
 Belt 1 Belt 2 Belt 3 Belt 4 Belt 5 Belt 6 Belt 7

Belt connection endless welded (only Transilon belt)  
 screwed overlapping connection

**Toothed wheel** or drive shaft  mm diameter

**Pins**  mm diameter  
 mm length or:  mm protruding pin length

Pin design standard Pins in gearing with other belts or shafts? Yes No  
 stainless steel (upon request)

Pin angle  degree Position of pins staggered in rows  
 degree

Pin pitch = Distance pin to pin  mm Distance from end of lath to first pin

	left mm	right mm	number pins
Lath 1	<input type="text"/>	<input type="text"/>	<input type="text"/>
Lath 2	<input type="text"/>	<input type="text"/>	<input type="text"/>

Specialities

Inquiry from	<input type="text"/>	Georg Koinzer GmbH & Co. KG Robert-Bunsen-Straße 15 36179 Bebra  Phone +49 6622 - 9284 - 0 Email sales@gkoinzer.de
Street	<input type="text"/>	
Zip code/location	<input type="text"/>	
Contact person	<input type="text"/>	
Phone	<input type="text"/>	
Email	<input type="text"/>	