

Questionnaire - Spiked Lattice PKS3020

Machine Type Part-No.
 Manufacturer Year

Inner length of **belt** mm measured over shafts Distance lath centre mm Standard
 - lath centre

Length of **laths** mm

Web strips between laths for sealing? yes (standard) no


Lath ends Polyamid caps standard
Laths straight ended

Number of **belts** pieces

Belts Transilon belt
Toothed belt
Toothed belt with intermediary

Width of belts mm

Division of belts middle - middle equal distribution and flush on the outside according to special design:



Endless connection endless welded
screwed overlapping connection

Pins	dimension	protruding pin length	overall height transilon	overall height toothed belt
	4 x 45 mm	approx. 21 mm	approx. 38 mm	approx. 42 mm
	4 x 55 mm	approx. 31 mm	approx. 45 mm	approx. 49 mm
special design upon request				

Pin design standard stainless steel (on request) sheradized (=very durable galvanization) Pins in gearing with other belts or shafts? Yes No

Pin degree degree
 degree

Position of pins staggered in rows

Pin pitch = Distance pin to pin mm

	left mm	right mm	number of pins
Lath 1	<input type="text"/>	<input type="text"/>	<input type="text"/>
Lath 2	<input type="text"/>	<input type="text"/>	<input type="text"/>

Specialities

Inquiry from	<input type="text"/>	Georg Koinzer GmbH & Co. KG Robert-Bunsen-Straße 15 36179 Bebra Phone +49 6622 - 9284 - 0 Email sales@gkoinzer.de
Street	<input type="text"/>	
Zip Code/location	<input type="text"/>	
Contact person	<input type="text"/>	
Phone	<input type="text"/>	
Email	<input type="text"/>	